



Wash It.



- Comprehensive Circul-Air Turnout Extractor System
- Fire-Specific Programming; NFPA 1850 (2026) Compliant
- Advance Cleaning Cycles; Specialized Cleaning Cycles
- Easy, Out-Of-The-Box Installation and Use
- Industrial Grade Construction; Soft Mount Configuration
- Used by Fire Stations and ISPs Across North America
- Includes Pre-Configured Dosing Pump and Detergent



Genius PRO Series

4-27 Pieces



	CACSGHD-23-PRO	CACSGHD-30-PRO	CACSGHD-45-PRO
Mount Method	Soft Mount	Soft Mount	Soft Mount
Unit Capacity (lbs/pieces)	23/4	30/6	45/8
Dimensions (wxdxh in inches)	27x31.6x46.3	31.3x36.8x52.4	34.3x38.4x56.4
Unit Weight (lbs)	377	697	906
Unit Door Opening (in)	14.8	14.8	18.5
Unit Floor to Door (in)	15.5	19.9	20.5
Electrical Configuration	120/60/1, 3-prong cord, 15	208-240/60/1/ 2w+G, 10	208-240/60/1/ 2w+G
Electrical Circuit Breaker	15	15	15
Water Supply Inlets	2 @ 3/4	2 @ 3/4	2 @ 3/4
Water Supply Flow (gpm)	16	16	34
Water Supply (psi)	29-87	29-87	29-87
Water Drain (method/size)	Pumped Wall or Gravity/3"	Gravity/3"	Gravity/3"
Unit Drum Volume (ft ³)	3	4.4	6.2
	CACSGHD-60-PRO	CACSGHD-70-PRO	CACSGHD-80-PRO
Mount Method	Soft Mount	Soft Mount	Soft Mount
Unit Capacity (lbs/pieces)	60/12	70/14	80/16
Dimensions (wxdxh in inches)	38.4x45.7x57.9	38.4x49x57.9	40.8x49.2x58.2
Unit Weight (lbs)	1299	1381	1477
Unit Door Opening (in)	18.5	18.5	18.5
Unit Floor to Door (in)	21.8	21.8	22.1
Electrical Configuration	208-240/60/1/ 2w+G (3 phase available)	208-240/60/1/ 2w+G (3 phase available)	208-240/60/3/3w+G, 10
Electrical Circuit Breaker	15	15	15
Water Supply Inlets	2 @ 3/4	2 @ 3/4	2 @ 3/4
Water Supply Flow (gpm)	34	34	34
Water Supply (psi)	29-87	29-87	29-87
Water Drain (method/size)	Gravity/3"	Gravity/3"	Gravity/3"
Unit Drum Volume (ft ³)	8.4	9.7	11.3

Contact the Circul-Air Sales Team for CACSGHD extractors in 90 lb and 130 lb configurations

Web: circul-air-corp.com • Email: sales@circul-air-corp.com • Phone: 1-800-795-1150 op. 2