



Dry It.



1 - NO HEAT
2 - OUTER SHELLS
3 - LINERS/HOODS
4 - GENERAL, NON-PPE DRY



- Comprehensive Circul-Air Turnout Dryer System
- Equipped with Moisture-Sensing Technology
- Pre-Programmed With NFPA 1850 Compliant Cycles
- Electric and Gas Operation
- Commercial Grade Construction
- 180-Degree Wide Door for Easy Loading
- Used by Fire Stations and ISPs Across North America



Tumble Dryer Series

4-25 Pieces



| | CACTD-25-35 | CACTD-55-65 | CACTD-75-85 | CACTD-115-125 |
|--------------------------------|---------------------------|---------------------------|---------------------------|-------------------------------|
| Capacity (lbs/pieces) | 35/8 | 65/14 | 85/18 | 125/25 |
| Door Diameter (in) | 22.7 | 26.9 | 27 | 27 |
| Door to Floor (in) | 27.5 | 26.3 | 29.2 | 31.4 |
| Drum Depth (in) | 30 | 35 | 36 | 41 |
| Drum Volume (ft ³) | 9.6 | 17.3 | 22.4 | 36.1 |
| Electrical Configuration | 120/1/50- 60/1W+N+G/15 | 120/1/50- 60/1W+N+G/15 | 120/1/50- 60/1W+N+G/15 | 208-240/3/50- 60/3W+N+G/15 |
| Gas Inlet (bsp) | ½ NPT | ½ NPT | ½ NPT | 1 NPT |
| Exhaust | 6 | 8 | 8 | 10 |
| Max Airflow (cfm) | 500 | 700 | 800 | 1400 |
| Dimensions (wxdxh in inches) | 27.9x45.5x63.9 | 34.5x53.1x66.7 | 38.5x53x77.3 | 46.1x67.9x85.7 |
| Weight (lbs) | 340 | 440 | 730 | 1250 |